

# APPLE

EQUIPMENT

FOR QUALITY ROAD CONSTRUCTION



## BITUMENT SPRAYER

Bitumen Sprayer Bitumen Pump 2" x 2" Size positive displacement gear pump with output 350 Liters / Min. (Max). Air Compressor Make - ELGI 2 CYL, 3 H.P. working pressure 9 kg. / cm 2 13.25m 3 Capacity 360 LPM. 550 R.P.M. Driving Unit Kriposker / HTC Vertical air Cooled diesel engine. Bitumen Spraying Pressure 0 to 6 Kg. / cm 2 Operator Platform Technometer: Slow Speed 0.5 Meter / Min. Temperature Gauge 0 - 250°C at front of tank Spray Bar

### PRODUCT SPECIFICATION

Model	ATM - 3000	ATM - 4000	ATM - 6000	ATM - 7000
Length	2100 mm	2400 mm	3100 mm	3300 mm
Width	1800 mm	1800 mm	1900 mm	1900 mm
Height	1500 mm	1500 mm	1550 mm	1650 mm
Capacity	3000 Ltrs	4000 Ltrs	6000 Ltrs	7000 Ltrs
Man Holer	600 mm	600 mm	600 mm	600 mm
Insulation	50 mm	50 mm	50 mm	50 mm
Fual Consumption of Burner	20 Ltrs. / Hr.	20 Ltrs. / Hr.	20 Ltrs. / Hr.	20 Ltrs. / Hr.
Burner	Compressed Air Type	Compressed Air Type	Compressed Air Type	Compressed Air Type
Burner Fuel Tank	50 Ltrs.	50 Ltrs.	50 Ltrs.	50 Ltrs.
Mounting	Ashok Leyland or Tata	Ashok Leyland or Tata	Ashok Leyland or Tata	Ashok Leyland or Tata
Bitumen Tank Shape	Rectangular Ovel Shape	Rectangular Ovel Shape	Rectangular Ovel Shape	Rectangular Ovel Shape

### PRODUCT SPECIFICATION

- **Bitumen Pump**  
2" x 2" Size positive displacement gear pump with output 350 Liters / Min. (Max).
- **Air Compressor**  
Make - ELGI 2 CYL, 3 H.P. working pressure 9 kg. / cm2 13.25m3 Capacity 360 LPM. 550 R.P.M.
- **Driving Unit**  
Kriposker / HTC Vertical air Cooled diesel engine.
- **Bitumen Spraying Pressure**  
0 to 6 Kg. / cm2
- **Operator Platform**  
Technometer: Slow Speed 0.5 Meter / Min.
- **Temperature Gauge**  
0 - 250°C at front of tank

# APPLE

EQUIPMENT

Office & Works :

Plot No : 294, GIDC, Estate, Phase-II, Dediyaan, Mehsana -2. Gujarat (INDIA).  
Ph: (02762) 224773 • Telefax: (02762) 255752 • Mo : +91 98259 90383  
E-mail: ferozashikh@yahoo.co.in • Website: www.appleequipments.com